

CLAIMS

- 1 1. An apparatus comprising:
2 at least one processor;
3 a memory coupled to the at least one processor;
4 a directory service server that accesses a directory that has a plurality of entries,
5 the plurality of entries including at least one proxy entry that contains security
6 information for a corresponding protected resource, the directory service server including
7 authentication and authorization functions that determine whether a selected one of the
8 plurality of entries may be accessed;
9 a plurality of protected resources that are not stored or contained within the
10 directory;
11 an application residing in the memory and executed by the at least one processor,
12 the application including a logical mapping that correlates each protected resource with a
13 corresponding proxy entry, the application determining whether the application is
14 authorized to access a selected protected resource by invoking the authentication and
15 authorization functions in the directory service server to determine whether the proxy
16 entry corresponding to the selected resource may be accessed, and if so, the application
17 accesses the selected protected resource.
- 1 2. The apparatus of claim 1 wherein the directory service server is a Lightweight
2 Directory Access Protocol (LDAP) server, and wherein the directory is an LDAP
3 directory.
- 1 3. The apparatus of claim 1 wherein the application does not access the selected
2 protected resource if the proxy entry corresponding to the selected resource cannot be
3 accessed.

- 1 4. A method for a directory service that contains a proxy entry corresponding to an
2 external protected resource to provide authentication and authorization functions to a
3 software application, the method comprising the steps of:
- 4 (A) when the software application needs to access the external protected resource,
5 performing the steps of:
- 6 (A1) identifying a proxy entry that corresponds to the external protected
7 resource;
- 8 (A2) the software application requesting from the directory service access
9 to the proxy entry that corresponds to the external protected resource; and
- 10 (A3) if the directory service grants access to the proxy entry that
11 corresponds to the external protected resource, the application accesses the
12 external protected resource.
- 1 5. The method of claim 4 further comprising the step of:
- 2 (A4) if the directory service denies access to the proxy entry that
3 corresponds to the external protected resource, the application does not access the
4 protected resource.

1 6. A method for a directory service to provide authentication and authorization
2 functions to a software application, the method comprising the steps of:
3 (A) determining which of a plurality of resources require protection;
4 (B) creating a proxy entry in the directory service for each protected resource;
5 (C) generating a logical mapping that correlates each protected resource to its
6 corresponding proxy entry;
7 (D) when the software application needs to access a selected protected resource,
8 performing the steps of:
9 (D1) using the logical mapping to identify a proxy entry that corresponds
10 to the selected protected resource;
11 (D2) the software application requesting from the directory service access
12 to the identified proxy entry; and
13 (D3) if the directory service grants access to the identified proxy entry, the
14 application accesses the selected protected resource.

1 7. The method of claim 6 further comprising the step of:
2 (D4) if the directory service denies access to the proxy entry that
3 corresponds to the selected protected resource, the application does not access the
4 selected protected resource.

